


Fast assembly concealed hinge

- ▶ Mounting plates with oblong hole height adjustment
- ▶ For Sensys in obsidian black


Cross mounting plate with premounted Euro screws



- ▶ For ø 5 x 12 mm holes
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment ± 3 mm
- ▶ Steel in obsidian black

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 091 799	9 091 800	9 091 801	9 091 802	50 ea.
37	9 307 977	9 307 978	9 307 979		200 ea.


"Hettich Direkt" cross mounting plate with locating pin and special screws



- ▶ For ø 5 x 7.5 mm holes
- ▶ Quality classification under EN 15570, Level 2
- ▶ Hole spacing 32 mm
- ▶ Half overlay door, from 15 mm side panel thickness
- ▶ Oblong hole height adjustment ± 2 mm
- ▶ Steel in obsidian black

Hole line distance LR mm	Order no. / Distance D mm				PU
	0.0	1.5	3.0	5.0	
37	9 091 807	9 091 808	9 091 809	9 091 810	50 ea.

Linear mounting plate for screwing on



- ▶ For ø 3.5 x 16 mm countersunk screws
- ▶ Quality classification under EN 15570, Level 3
- ▶ Oblong hole height adjustment ± 1.6 mm
- ▶ Die-cast zinc in obsidian black

Hole line distance LR mm	Order no. / Distance D mm		PU
	0.5	3.0	
20	9 091 815	9 091 816	50 ea.
20	9 308 038		200 ea.